


**Data Sheet**



**Type Number** ..... 6214  
**Designation IEC** ..... CR 17335  
**System** ..... Li-Manganese dioxide / Organic Electrolyte

**UL Recognition** ..... MH13654  
**Nominal Voltage** ..... 3 V  
**Typical Capacity C** ..... 1600 mAh  
Current 1 mA , at 20°C down to 2 V  
**Maximum cont. Discharge**..... 1500 mA  
**Maximum Pulse Discharge**..... 3500 mA

**Weight (approx.)** ..... 17 g  
**Volume** ..... 7 ccm  
**Coding**..... Date of Manufacturing Quarter / Year

<b>Temperature Ranges</b>	min	max.
Storage .....	-20°C	45 °C
Discharge .....	-40°C	70 °C *

<b>Dimensions</b>	min	max.
Diameter (A) .....	16,2	16,8
Height (B) .....	32,5	33,5
Shoulder Diameter[L].....	6,3	
Shoulder Height [M].....	0,5	

**Typical Capacities (at 20°C)**


Discharge Type	Discharge	End Voltage: 2.0 V
Continuous 24h/7d/w	1mA	Capacity [mAh]: 1600

\* Contact VARTA if the application is intended to be outside the range of -20°C to +60°C.


*Information and contents in this data sheet are for reference purpose only.  
They do not constitute any warranty or representation and are subject to change without notice.  
For most current information and further details, please contact your VARTA representative.*

**Data Sheet**


• **Temperature Characteristics**



• **Pulse discharge characteristics**



• **Discharge Characteristics**



- Self-discharge rate < 1%/Y at room temperature
- Storage life > 10 years
- Operating life\* > 10 years

\* depending on environmental condition and energy consumption

*Information and contents in this data sheet are for reference purpose only.  
They do not constitute any warranty or representation and are subject to change without notice.  
For most current information and further details, please contact your VARTA representative.*